

TYP	Max. napětí	Napětí při odporu 500 Ohm	Max. vybijecí energie	Orientační max. délka ohrady				Min. počet zemních tyčí	Cena bez DPH	Cena s DPH
				Teoretická podle normy	Bez porostu	Se středním porostem	S velkým porostem			
N 700	10000 V	4000 V	1 J	20 km	3 km	0,8 km	-	1	1666,-	2000,-
CAVALLO N 1001	12300 V	4500 V	1,6 J	20 km	5 km	1 km	-	1	2000,-	2400,-
CAVALLO N 2002	11300 V	5200 V	2,6 J	60 km	15 km	3 km	1,5 km	2	2700,-	3240,-
Minotor	10500 V	5800 V	5 J	110 km	28 km	7 km	3 km	2	2900,-	3480,-
PP NI 7000	11600 V	8400 V	7 J	230 km	70 km	15 km	7,5 km	3	4600,-	5520,-
PP NDI 10000 Digital	11600 V	8600 V	16,5 J	300 km	80 km	18 km	9 km	3	6900,-	8280,-
PP NDI 15000 Digital	11700 V	8800 V	20 J	350 km	100 km	22 km	12 km	3	7900,-	9480,-
CAVAL 2	8000 V	3000 V	2 J	60 km	15 km	3 km	1,5 km	2	2000,-	2400,-
CLOS 2000	10000 V	3800 V	4 J	100 km	26 km	5 km	2,5 km	2	2800,-	3360,-
SECUR 2500	12000 V	3800 V	6 J	160 km	55 km	6 km	5,5 km	3	4000,-	4800,-
UBISON 10000	10000 V	5600 V	10 J	300 km	80 km	18 km	9 km	3	6300,-	7560,-
UBISON 15000	10000 V	8200 V	15 J	355 km	110 km	24 km	14 km	3	8800,-	10560,-
MBX 1500	8000 V	3000 V	3 - 12 J	320 km	90 km	10 km	11 km	3	13800,-	16560,-
M 600	8800 V	3500 V	5 J	140 km	45 km	8 km	4,5 km	3	6500,-	7800,-
M 300	7900 V	3000 V	2 J	60 km	15 km	3 km	1,5 km	3	5500,-	6600,-
Farm Master	8700 V	3500 V	3 J	90 km	25 km	4,5 km	2 km	2	4750,-	5700,-
Equi Master	8000 V	3000 V	2 J	60 km	15 km	3 km	1,5 km	2	3250,-	3900,-